








# Tensitron Meter Selection

## Tensitron Tension Meter Applications

METER (PRODUCT LINE)	TR/ TX-1	<b>Thin Wire, Filaments, Tape</b> STATIC OR DYNAMIC 0 - 5,000 g Tension	
	STX-1		<b>Strap or Wire</b> STATIC ONLY 2 - 909 kgs Tension
	ACM/ ACX-1	<b>Flexible Cable up to 1/4"</b> STATIC ONLY 2 - 227 kgs Tension	
	LX-1	<b>Medium Cable, Wire, Strap</b> STATIC OR DYNAMIC 2 - 227 kgs Tension	
	BTM	<b>Bands and Belts up to 3" Wide and 1/8" Thick</b> STATIC OR DYNAMIC 2 - 227 kgs Tension	
	WC		<b>Flat Web up to 1/8" Thick</b> STATIC OR DYNAMIC 10 - 454 kgs Tension
	CX-1		<b>Flexible Wire Rope up to 3/4"</b> STATIC OR DYNAMIC 5 - 909 kgs Tension
		1g.    1 kg    2 kg    5 kg    10 kg    250 kg    500 kg    1000 kg <b>TENSION</b>	

This chart shows example applications for Tensitron meters. Use it to help select the right product line. Then see the product data sheet for details.